



Chevron Conveyor Belt

花纹输送带

> > Features 特点

A conveyor belt composed of patterned rubber covering the working surface, flat rubber covering the non working surface, and tire body. Due to differences in the transportation materials and the inclination angle of the conveyor, the shape, height, and depth of the patterns vary. Pattern forms: herringbone, concave pit, U-shaped, etc.Can be customized according to customer needs.

由工作面上的花纹覆盖橡胶、非工作面的平覆盖橡胶和胎体组成的输送带。因运输材料和输送机倾斜角度的差异，图案的形状、高度和深度各不相同。花纹形式：人字型，凹坑型，U型等。可根据客户需求定制。

> > Applications 用途

Widely applicable to mining and quarrying, agriculture and food processing, construction, port and logistics industries.
Herringbone pattern: High friction, suitable for steep-angle and heavy-load transportation (e.g., mining).
Fishbone pattern: Prevents lateral slippage, used for loose materials (e.g., sand and soil).
Diamond pattern: Multi-directional anti-slip, commonly seen in agriculture and packaging lines.
Strip/Wave pattern: Guides drainage, suitable for washing and food processing in wet environments.



广泛适用于采矿和采石、农业和食品加工、建筑、港口和物流行业。
人字形花纹：高摩擦，适用于陡坡和重载运输（如采矿）。
鱼骨图案：防止横向滑动，用于松散材料（如沙子和土壤）。
钻石图案：多向防滑，常见于农业和包装生产线。
条形/波浪形：引导排水，适用于潮湿环境中的洗涤和食品加工。

花纹类型及参数：Pattern type and parameters

Chevron Type	Pattern	C.H(m m)	C.W(mm)	C.P (mm)	Belt Width	
					mm	inch
C6	C6-P230	6	230	75	300-400	12" - 16"
	C6	6	300-1200	100	300-1200	12" - 48" (1215)
V6	V6	6	600-1800	75	600-1800	24" - 72"
C12	C12-V800	12	800	150	800-1200	32" - 48" (1206)
C15	C15-V330	15	330	250	400-600	16" - 24"
	C15-P385	15	385	250	500-800	20" - 32" (800)
	C15-V450	15	450	300	600-600	24" - 32" (800)
	C15-P500	15	500	340	550-750	22" - 30" (750)
	C15-P600	15	600	250	750-1000	30" - 40"
	C15-P750	15	750	250	900-1200	36" - 48" (1215)
C25	C25-P450	25	450	335	600-750	24" - 30" (750)
	C25-P550	25	550	250	600-800	24" - 32"
	C25-P750	25	750	330	900-1200	36" - 48" (1215)
Y32	Y32-P450	32	450	255	500-800	20" - 32" (800)
	Y32-P600	32	600	300	800-1000	32" - 36"
	Y32-P800	32	800	333	1050-1200	36" - 48"