



Sidewall Conveyor Belt

挡边输送带

> > Features 特点

It has the characteristics of strong lateral rigidity, tear resistance, flexural resistance, fatigue resistance, and flexible angle transformation, with high conveying efficiency. Especially suitable for conveying bulk materials. In addition, it also has the advantages of low maintenance costs and small footprint.

拉伸强度大，抗冲击性好，寿命长，使用伸长率小，成槽性好，耐曲挠性好，适用于长距离，大运量、高速度物料输送。

> > Applications 用途

Widely applicable to ports, docks, metallurgy, mining, building materials, cement, chemical industry and other fields. Advantages such as significantly reducing the investment cost of buildings.

广泛适用于港口、码头、冶金、矿山、建材、水泥、化工等领域。可大幅度降低建筑物的投资成本等优点。



挡边带配备的输送机输送能力m/h(v=1m/s带宽=1000mm)

The shifting capacity of transfer with apron m/h(v=1m/s Belt width=1000mm)

倾角°	挡边高mm 输送能力m³/h 挡板间距mm		120	160	200	倾角°	挡边高mm 输送能力m³/h 挡板间距mm		120	160	200
30	160	148	336	436	500	70	125	90	203	278	352 281 306
	200	128	273	402			160	72	159	224	
	250	98	218	360			200	61	129	182	
	330	76	168	290			250		107		
	500						330				
35	125	165	305	376 326 251	471 390 259	75	160	81	184	252	316 250
	160	130	200				200	63	143	201	
	200	102	231				250	53	115	169	
	250	95	187				330		95	134	
	330	75	156				500				
40	125	145	286	346 288 218	430 304	80	125	73	164	224 182 146	283 226 172
	160	113	223				160	57	125		
	200	95	204				200	44	106		
	250	85	162				250		86		
	330	65	137				330				
50	125	113	247	35 278 228 176	422 347 273	85	125	66	125	175 137 113 87	217 175 136
	160	85	176				160	42	97		
	200	70	146				200	34	80		
	250	60	127				250		66		
	330	45	95				330				
60	125	110	246	339 274 218 173	110 85 70	90	125	53	124	215 171 133	
	160	85	195				160	46	97		
	200	70	153				200	38	83		
	250		129				250		67		
	330						330				
	500						500				




GB/T9770 标准中覆盖胶性能等级 Rubber performance levels in GB/T9770 standard

挡边型号	挡边高度 mm	底脚宽 mm	波距mm	配用隔板	底脚宽 mm
S	40	30	57	T35	T35
S	60	50	42	T55	T55
S	80	50	42	TC75	TC75
S	100	50	42	TC90	TC90
S	120	50	42	TC110	TC110
S	160	75	63	TC140	TC140
S	200	75	63	TC180	TC180
S	240	75	63	TC220	TC220
S	300	100	84	TC260	TC260
S	400	100	84	TCS360	TCS360
S	500	125	105	TCS460	TCS460
S	630	125	105	TCS580	TCS580

挡边带配备的输送机输送能力m/h(v=1m/s带宽=1000mm)

The shifting capacity of transfer with apron m/h(v=1m/s Belt width=1000mm)

基带宽B Bandwidth B base	基带高H block high H	横隔板高H1 horizontal baffle high H1	波底宽B1 the wave bottom wide B1	有效带宽B2 effective bandwidth B2	空边宽B3 empty wlde B3	横隔板形状 Horizontal naffle form
300	40	35	25	180	35	TC
	60	55	50	120	40	
	80	75				
400	60	55	50	180	60	TC
	80	75				
	100	90				
500	80	75	50	250	75	TC
	100	90				
	120	110				
650	100	90	50	350	100	TC
	120	110				
	160	140				
800	120	110	50	460	120	TC
	160	140	75	410		
	200	180				
1000	160	140	75	550	150	TC
	200	180				
	240	220				
1200	160	140	75	690	180	TC
	200	180				
	240	220				
	300	360				
1400	200	180	75	830	210	TC
	240	220				
	300	260				
	400	360	100	780		



T型



C型



TC型



TS型



TCS型